

cnMatrix™ EX3024F Switch

Intelligent Ethernet Fiber Aggregation Switching

QUICKLOOK :

- **Zero-touch deployments**
- **Policy Based Automation**
- **Auto device profiling and segmentation**
- **Non-blocking, line-rate architecture with fully featured L2/L3 switching**



Cambium Networks' next generation switching platform offers a cloud managed, high performance, feature rich enterprise grade ethernet switching solution.

The cnMatrix platform of switches provides:

- Easy and simple, free cloud (or on premise) management with cnMaestro™ or XMS
- Zero-touch deployment of switches makes installation easy
- Policy Based Automation eliminates manual and time consuming configuration
- Enhanced Security with automated device profiling and segmentation
- Policy Based Automation eliminates manual configuration during adds, moves and changes of network devices
- Unified Wired-Wireless access solution

The cnMatrix series of fully managed switches delivers full Layer 2 and Layer 3 capabilities with enhanced access security. The EX3024F is a fiber aggregation switch that has all 10Gbps SFP+ fiber ports. Also, this switch has dual internal power supplies for additional robustness and redundancy. These switches come with a 5-Year Limited Lifetime Warranty



cnMaestro



XMS



cnMatrix EX3024F Switch

Specifications

Throughput	480 Gbps	Flash Storage	256 MB
Forwarding Rate in Mpps (64 Byte Packets)	120	DRAM	1 GB
10/100/1000 Ports	n/a	VLANs	4K
2.5 G Ports	n/a	QinQ	Yes
Fiber Ports	24 SFP+	LACP/Trunking	8 LAGs/8 links per LAG
PoE+ Enabled Ports 802.3af/at	N/A	QoS Priority Queues	8
PoE+ Enabled Ports 802.3af/at/bt	n/a	PVRST	32 (128 future)
Serial Console	✓	Ingress/Egress ACL	128
USB	✓	Static ARP Entries	512
Out-of-Band Management Port	✓	ARP Entries	512
Rack Mount Kit	✓	Static Routes	64
Internal Fans	2	Dynamic Routing	512 (2K future)
Reset Button	✓	IGMP Multicast Groups	256 (1K future)
MAC Address Table Size	16K	Policy Based Automation	✓

* Feature to be included in a future release.

cnMatrix EX3024F Switch

Specifications - All Models

Quality of Service	ACL mapping and marking of ToS/DSCP (COS)	Layer 2 Feature Set	802.1s multiple spanning tree
	ACL mapping marking of 802.1p		VLAN, Port, Protocol, 802.1q
	ACL mapping to priority queue		QinQ*
	DiffServ support		802.1d
	Honoring DSCP and 802.1p (CoS)		802.1x authentication
	Traffic shaping/metering		Auto MDI/MDIX
	Priority queue management using Weighted Round Robin (WRR), Strict Priority (SP) and a combination of WRR and SP		BPDU Guard, Root Guard
Traffic Management	ACL-based inbound rate limiting policies		IGMP Snooping v1/v2/v3*, Fast Leave
	Broadcast, multicast and unknown unicast rate limiting		LLDP/LLDP MED
	Inbound rate limiting per port		IGMP Proxy
	Outbound rate limiting per port/queue		Static MAC
Security	802.1x authentication		Flow Control per port
	MAC authentication*		Per VLAN STP (PVST/PVRST)
	DHCP snooping		Port Mirroring: port based, ACL based, VLAN based
	RADIUS authentication/authorization	Port Isolation/Private VLAN Edge	
	Radius/Tacacs/Tacacs+	Link Aggregation Groups (Static/LACP)	
	Authentication, Authorization, and Accounting (AAA)	Rate Limiting/Storm Control	
	Secure shell	Jumbo frame (9k)	
	Secure copy (SCP)*	DHCP Snooping	
	Local username/password	BPDU filtering	
		Broadcast/Multicast/Unlearned Unicast (Storm Control)	
	DoS Protection		
	Ping/TraceRoute/ICMPv6		

* Feature to be included in a future release.

Layer 3 Feature Set

Inter-VLAN Routing

Static ARPs

Static Routes

DHCP Relay

Dynamic Routing – RIPv1/v2

Dynamic Routing – OSPFv2

Route Redistribution

cnMatrix EX3024F Switch

Specifications - All Models cont'd

Management

cnMaestro or XMS (cloud management)	Simple Network Time Protocol (SNTP)
Industry standard Command Line Interface (CLI)	Local/remote system logging
DHCP Client	Policy Based Automation
Embedded web management (HTTP/HTTPS)	Display log messages multiple terminals*
Embedded DHCP server	TFTP/SFTP
USB file management and storage	Telnet client/server
Out-of-Band Ethernet Management	IPv6 management
SSH / SSH v2	Password management
SNMP v1/v2/v3	Autoinstall support for firmware images and config files
DHCP relay	

Security

PERMIT/DENY ACTIONS FOR INBOUND IP AND LAYER 2 TRAFFIC CLASSIFICATION BASED ON:

Source/Destination IP address	EtherType
TCP/UDP Source/Destination port	IEEE 802.1p user priority
IP Protocol Type	VLAN ID
Type of Service (ToS) or differentiated services (DSCP) field	RFC 1858—Security Considerations for IP Fragment Filtering
Source/Destination MAC address	

* Feature to be included in a future release.

Hardware Specifications

Power Supply	Dual internal 120W
Max Switch Power (WITH TRAFFIC)	TBD
MTBF (Hours)	TBD
Weight	TBD
Dimensions	TBD
CPU Speed	TBD
LEDs Per Port	Link/Activity

PoE+ Power Budget	n/a
PoE + Voltage	n/a
PoE Max Power Per Port	n/a
Rack Mountable	Yes 1U
Temperature Ranges	0°C to 50°C (32°F to 122°F)
Operating Humidity	55° at 95% RH
Storage Temperature	-40°C to 70°C (-40°F to 158°F)

Acoustic Noise dBA Per Switch (AMBIENT TEMPERATURE)

TBD TBD

cnMatrix EX3024F Switch

IEEE Standards

Switching

Core Switching Features

IEEE 802.1ab—Link Layer Discovery Protocol (LLDP)
IEEE 802.1D—Spanning tree compatibility
IEEE 802.1p—Ethernet priority with user provisioning and mapping
IEEE 802.1s—Multiple spanning tree compatibility
IEEE 802.1Q—Virtual LANs with port-based VLANs
IEEE 802.1X—Port-based authentication

VLAN Support

IEEE 802.1W—Rapid spanning tree compatibility
IEEE 802.3—10BASE-T
IEEE 802.3u—100BASE-T
IEEE 802.3ab—1000BASE-T
IEEE 802.3ac—VLAN tagging
IEEE 802.3ad—Link aggregation
IEEE 802.3x —Flow control
Bridged Local Area Networks - Amendment 07: Multiple Registration Protocol

IEEE 802.1Q-2003

RFC 4541—Considerations for Internet Group Management Protocol (IGMP) Snooping Switches

ANSI/TIA-1057—LLDP-MEDia Endpoint Discovery (MED)

Advanced Layer 2 Features

Authentication, Authorization, and Accounting (AAA)
IEEE 802.1ad (QinQ)*
Broadcast/Multicast/Unknown unicast storm recovery
DHCP Snooping
IGMP Snooping Querier
Independent VLAN Learning (IVL) support
Jumbo Ethernet frame support
Port MAC locking
Port mirroring
Protected ports
Static MAC filtering

Layer 3 Features

Inter-VLAN Routing
Static ARP
Static Routes
RFC 2131 – DHCP Relay
RFC 2328 – OSPF Version 2
RFC 2453 – RIP Version 2

* Feature to be included in a future release.

cnMatrix EX3024F Switch

System Facilities

Event and error logging facility

Run-time and configuration download capability

PING utility

FTP Transfers via IPv4/IPv6

RFC 768—UDP

RFC 783—TFTP

RFC 791—IP

RFC 792—ICMP

RFC 793—TCP

RFC 826—ARP

RFC 894—Transmission of IP datagrams over Ethernet networks

RFC 896—Congestion control in IP/TCP networks

RFC 951—BOOTP

RFC 1034—Domain names - concepts and facilities

RFC 1035—Domain names - implementation and specification

RFC 1321—Message digest algorithm

RFC 1534—Interoperability between BOOTP and DHCP

RFC 2021—Remote network monitoring management information base version 2

RFC 2030—Simple Network Time Protocol (SNTP)

RFC 2132—DHCP options and BOOTP vendor extensions

RFC 2819—Remote Network Monitoring Management Information Base

RFC 2865—RADIUS client

RFC 2869—RADIUS Extensions

RFC 3579—RADIUS support for EAP

RFC 3580—IEEE 802.1X RADIUS usage guidelines

RFC 3164—BSD syslog protocol

RFC 3580—802.1X RADIUS Usage Guidelines

* Feature to be included in a future release.

Management

SNMP v1, v2, and v3

SSH 1.5 and 2.0

RFC 4252—SSH authentication protocol

RFC 4253—SSH transport layer protocol

RFC 4254—SSH connection protocol

RFC 4251—SSH protocol architecture

RFC 4716—SECSH public key file format

RFC 4419—Diffie-Hellman group exchange for SSH transport layer protocol

SSL 3.0 and TLS 1.0

RFC 2246—TLS protocol, version 1.0

RFC 2818—HTTP over TLS

RFC 3268—AES cipher suites for transport layer security

Telnet

Web GUI

cnMatrix EX3024F Switch

SNMP MIBs

Enterprise MIBs for Full Configuration Support of Switching Features

RFC 1213—MIB II

RFC 1493—Bridge MIB

RFC 1612—DNS resolver MIB extensions

RFC 1643—Definitions of managed objects for Ethernet-like interface types

RFC 2233—Interfaces group MIB using SMI v2

RFC 2613—SMON MIB

RFC 2618—RADIUS authentication client MIB

RFC 2674—VLAN MIB

RFC 2737—Entity MIB version 2*

RFC 2819—RMON groups 1, 2, 3, and 9

RFC 2863—IF-MIB

RFC 2925—Definitions of Managed Objects for Remote Ping, Traceroute, and Lookup Operations

RFC 3273—RMON Groups 1, 2, and 3

RFC 3291—Textual conventions for Internet network addresses

RFC 3434—RMON Groups 1, 2, and 3

RFC 4022—TCP-MIB

RFC 4113—UDP-MIB

* Feature to be included in a future release.

Quality of Service MIBs

MIBs for full configuration support of DiffServ, ACL, and CoS functionality

RFC 3289—Management information base for DiffServ architecture (read-only)

Quality of Service

Classify Traffic Based on Same Criteria as ACLs and Optionally:

Mark the IP DSCP or Precedence header fields

Police the flow to a specific rate with two-color aware support

RFC 2474—Definition of the differentiated services field (DS field) in the IPv4 and IPv6 headers

RFC 2475—An architecture for differentiated services

RFC 2597—Assured forwarding Per-Hop Behavior

cnMatrix EX3024F Switch

cnMatrix Ordering Information

Type	Part Number	Description
Switch	MXEX3024xFxA00	cnMatrix EX3024F, Intelligent Ethernet Fiber Aggregation Switch, 24 - 10 Gbps SFP+ ports, dual internal AC power supplies - no power cord
Switch	MXEX3024xFxA01	cnMatrix EX3024F, Intelligent Ethernet Fiber Aggregation Switch, 24 10 Gbps SFP+ ports, dual internal AC power supplies - no power cord, USA only
Power Cord	N000900L040A	AC line cord, US Type B, 1.2m C13 Connector
Transceiver	SFP-10G-SR	10G SFP+ MMF SR Transceiver, 850 nm. -40°C to 85°C (-40°F to 185°F)
Transceiver	SFP-1G-SX	1G SFP MMF SX Transceiver, 850 nm. -40°C to 85°C (-40°F to 185°F)
Transceiver	SFP-10G-LR	10G SFP+ SMF LR Transceiver, 1310 nm. -40°C to 85°C (-40°F to 185°F)
Transceiver	SFP-1G-LX	1G SFP SMF LX Transceiver, 1310 nm. -40°C to 85°C (-40°F to 185°F)
Transceiver	SFP-1G-Copper	1000Base-T (RJ45) SFP Transceiver. -40°C to 85°C (-40°F to 185°F)
Transceiver	SFP-10G-Copper	10G Base-T (RJ45) SFP Transceiver. 0°C to 70°C (-40°F to 185°F)

Management & Advanced Care Ordering Information

Non-inventory Item	CCADV-SUP-EX3024F-1
Non-inventory Item	CCADV-SUP-EX3024F-3
Non-inventory Item	CCADV-SUP-EX3024F-5
Non-inventory Item	CCADV-UPG-EX3024F-1
Non-inventory Item	CCADV-UPG-EX3024F-3
Non-inventory Item	CCADV-UPG-EX3024F-5
Non-inventory Item	CCADV-UPG-RNW-EX3024F-1
Non-inventory Item	CCADV-UPG-RNW-EX3024F-3
Non-inventory Item	CCADV-UPG-RNW-EX3024F-5
Non-inventory Item	CCPRO-SUP-EX3024F-1
Non-inventory Item	CCPRO-SUP-EX3024F-3
Non-inventory Item	CCPRO-SUP-EX3024F-5
Non-inventory Item	MSX-SUB-EX3024F-1
Non-inventory Item	MSX-SUB-EX3024F-10
Non-inventory Item	MSX-SUB-EX3024F-3
Non-inventory Item	MSX-SUB-EX3024F-5

ABOUT CAMBIUM NETWORKS

Cambium Networks empowers millions of people with wireless connectivity worldwide. Its wireless portfolio is used by commercial and government network operators as well as broadband service providers to connect people, places and things. With a single network architecture spanning fixed wireless and Wi-Fi, Cambium Networks enables operators to achieve maximum performance with minimal spectrum. End-to-end cloud management transforms networks into dynamic environments that evolve to meet changing needs with minimal physical human intervention. Cambium Networks empowers a growing ecosystem of partners who design and deliver gigabit wireless solutions that just work.